



B-PROT-KEYPAD-2100

RFID-Keypad
BURGprotect KEYPAD 2100

PRODUCT DESCRIPTION

► Application:

Alarm message on interruption of the contact Easy installation, mounting without screws Suitable for windows and doors Message on low battery Compatible with the whole family of the BURGprotect series Battery included

► Technical specifications:

Type	Remote control
Supported software for remote access	BURGprotect App
Voltage	5 VDC (integ. Lithium-Ion Akku)
Max. current consumption	Activity: 65mA / Standby: 6 month
Max. Range (m)	Outdoor: 200m / Indoor: 50m
Transmission frequency (MHz)	433,92
Operating temperature (°C)	0 to +60
Rel. humidity (%)	Max. 95, non-condensing
Weight	162,3g (incl. Batterie)
Dimensions WxHxD (mm)	92 x 145 x 13
Items included in delivery	Power-Supply, battery, wall mount
Specials	The BurgProtect Base 2200 is needed

► Weitere Bilder:

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.



► Recommended Accessories

B-PROT-CONTROL-2110	Remote Control BURGprotect CONTROL 2110
B-PROT-MOTION-2010	Motion detector (passive) BURGprotect MOTION 2010
B-PROT-SMOKE-2050	Smoke detector BURGprotect SMOKE 2050
B-PROT-VIBRANCY-2020	Vibration sensor BURGprotect VIBRANCY2020
B-PROT-WATER-2060	Water sensor BURGprotect WATER 2060