



### SNC-841DBIAEH

4K/Ultra 8 MP HD bullet camera, ePoE  
2,7-12mm, (IVA+), heater

## PRODUCT DESCRIPTION

### ► Application:

SANTEC SNC-841-E series is a 8 MP bullet camera with integrated IR-LEDs and it is the perfect solution for all 24/7 indoor and outdoor applications. This IP camera has a weather-proof housing (IP-66) and is vandal-proof (IK10). Thanks to 8 megapixel resolution, the images are very clear hence no detail is undetected. Due to the auto focus lens and the web interface the camera is easy to adjust. The camera comes with features such as 3DNR for noise reduction, Wide Dynamic Range (WDR), ePoE and micro-SD card slot, to name but a few.

### ► Technical specifications:

Type	IP Day/Night IR bullet camera
Decoding / Video / Lens	>>>>DECODING/VIDEO/LENS<<<<<<
Sensor type	1/2.5" Progressive Scan CMOS
Max. Picture resolution (pixel)	UHD 8 MP (3840x2160)
Video codec	H.264, H.265, MJPEG, H.264+, H.265+
Max. frame rate (fps)	15fps@4K, 25fps@3MP
Number of video streams	3 (1x Main, 2x Sub)
Lens mount	Intern
Iris control	DC
S/N ratio (dB)	< 50dB
Lens type	4x autofocus lens
Focal length	2,7 - 12 mm / F1.4
Optical zoom	4x, adjustable
Angle of view (horizontal)	100° - 35°
Angle of view (vertical)	54° - 20°
Sensitivity (Lux)	0,05lx (color)

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com







**Note:**

SD card is not included.

► **Recommended Accessories**

SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug
SNCA-MK-4530	Adapter / Junction box for suitable for SANTEC cameras
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
SNCA-PM-4660	Pole Mount adapter up to 127 mm and SNCA-JB-4640 and SNCA-WM-4642 (SNC-211RSIA)
SNCA-CM-4670	Corner Mount Adapter for see recommended accessories
BWNET-10120	1-Kanal 30W PoE Netzteil 56V 30W Gigabit Active POE injector